

AIR OPERATED POPPET VALVES AND SPOOL VALVES

Product index



standards	ports/positions	function	pipe connections										pad mount	max. pressure (bar)	flow at 6 bar l/min (ANR)	type	illustration	series	page	
			NC	NO	6	1/8	1/4	3/8	1/2	3/4	1	1 1/4								1 1/2
VDMA/ISO15407-1 ISO 5599-1																				
Poppet valves																				
	3/2	● ●												⊥	12	700 1750	DM		261 262	3
	3/2	● ●													12	4500-6000	DH		284	05
														16	12500	DH	285			
														16	35000	DH	286			
	3/2	●												⊥	16	3000	DP		266	07
														⊥	16	9100	DP		267	
														⊥	16	31500	DP		268	
ISO	3/2	●												⊥	10	5675	ISO 3		G34	09
	4/2													⊥	16	2940	DP		266	15
														⊥	16	9100	DP		267	
														⊥	16	31500	DP		268	
	4/2														10	210 840			263 264	11
	4/2													⊥	12	700 1750	DM		261 262	13

00379GB-2017/R01
Availability, design and specifications are subject to change without notice. All rights reserved.

All leaflets are available on: www.asco.com

standards		ports/positions	function	pipe connections										pad mount	max. pressure (bar)	flow at 6 bar l/min (ANR)	type	illustration	series	page		
VDMA/ISO15407-1	ISO 5599-1			NC	NO					ØG												
Spool valves																						
		3/2	●													10	860 3000 3800			551 553	1	
		5/2																		551 553	23	
		3/2	●													8	400			519 520 521	17	
		5/2													175-1050							
		5/3													600-1050							
		5/2 5/3														10	1000-1700			L1 L2	19 21	
VDMA - ISO		5/2 5/3														⊥	8	500	ISO 02		CL18	25
	ISO	5/2 5/3														⊥	10/12	1400 2800 4200	ISO 1 ISO 2 ISO 3		541	27
																				542		
																				543		
	ISO	5/2 5/3														⊥	12	6300-7000	ISO 4		544	31
	ISO	5/2 5/3														⊥	10	1400 2800 4200	ISO 1 ISO 2 ISO 3		E12 E23 E34	33