



## Latitude Pro Arc Flash 7' Web SRL-P

\*See chart for part numbers, hook configurations, and product weights

### FEATURES :

- Complete confidence in full, continuous retraction with side payout housing.
- Reliable internal braking system eliminates need for external shock pack.
- 360/180° attachment point offers full range of motion.
- High strength semi-sealed assembly protects internal components from debris to extend product life.
- Translucent housing allows easy inspection of webbing, reserve line and pawl assembly.
- Trusted Kevlar® webbing and Nomex® flame-resistant label cover.
- Minimal exposed webbing protects against UV damage.
- Single leg and dual leg options available.
- Available with various hook and attachment options, see chart.
- All components are Z359.12 compliant.



Class  
**1**  
Anchor at or above dorsal D-ring

Product shown:  
020-5221

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66
ASTM	F887

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 23 in. (58 cm)
Max. free fall distance	24 in. (61 cm)
Use below d-ring	<b>NOT PERMITTED</b>
Min. required fall clearance	5 ft. 11 in. (1.8 m)
For full clearance requirements, see user instructions	

OSHA (BELOW D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 900 lbs. (408.2 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 23.6 in. (60 cm)
Max. free fall distance	48 in. (122 cm)
Use below d-ring	2 ft. (0.61 m)
Min. required fall clearance	8 ft. (2.4 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Webbing	20 mm Kevlar® webbing
Housing	Clear resin
Bracket	Steel, aluminum (dependent on configuration)
Hook options	Steel, aluminum, dielectric (dependent on configuration)



# Latitude Pro Arc Flash 7' Web SRL-P



Standards: ANSI Z359.14-2021

OSHA 1910.140, 1910.66

ASTM F887

Capacity: ANSI 130-310 lbs. (59-141 kg)

OSHA Up to 420 lbs. (191kg)

**CONNECTOR**

**ATTACHMENT**

Part Number	Single Leg (S) / Dual Leg (D)	Working Length (ft.)	Lifeline Material	Lifeline Dimensions (in.)	Housing Material	Weight (lbs.)	LI Steel Swivel Snap Hook	LI Steel Swivel Snap Hook	Dielectric Snap Hook	Steel Tie Back Hook	Steel Rear Hook	Steel Swivel Rebar Hook	Steel Swivel Rebar Hook	Steel Captive Eye Carabiner	ALU Swivel Carabiner	ALU Captive Eye Carabiner	ALU Captive Eye Carabiner	ALU Carabiner	ALU Snap Hook	Cab Mount Bracket	FS-E2413	Integrated BWB	Soft Loop	1014 BWB	9012 BWB	9013 BWB	
							①	②	③	④	⑤	⑥	⑦	⑧	⑨	⑩	⑪	⑫	⑬	⑭	⑮	⑯	⑰	⑱	⑲	⑳	㉑
020-5200	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	3.0	X									X										
020-5201	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	2.8					X					X										
020-5202	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	3.0		X								X										
020-5203	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	3.6							X			X										
020-5204	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	2.7	X																		X	
020-5205	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	3.7					X														X	
020-5206	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	2.5		X																	X	
020-5207	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	3.3							X												X	
020-5208	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	2.8			X																X	
021-5285	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	3.1			X							X										
020-5213	1	D	7	Kevlar® Webbing	.7X.05	Clear Resin	5.1	X																		X	
020-5214	1	D	7	Kevlar® Webbing	.7X.05	Clear Resin	7.1					X														X	
020-5215	1	D	7	Kevlar® Webbing	.7X.05	Clear Resin	4.7		X																	X	
020-5216	1	D	7	Kevlar® Webbing	.7X.05	Clear Resin	6.3							X												X	
020-5221	1	D	7	Kevlar® Webbing	.7X.05	Clear Resin	5.5			X																X	
020-5217	1	D	7	Kevlar® Webbing	.7X.05	Clear Resin	5.0	X																		X	
020-5218	1	D	7	Kevlar® Webbing	.7X.05	Clear Resin	7.1					X														X	
020-5219	1	D	7	Kevlar® Webbing	.7X.05	Clear Resin	4.7		X																	X	
020-5220	1	D	7	Kevlar® Webbing	.7X.05	Clear Resin	6.3							X												X	
022-5308	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	2.5			X												X					
022-5309	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	2.5							X					X								
022-5310	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	2.5							X					X								

