



DECLARATION OF CONFORMITY

DECLARATION DATE: 12/30/22
TEST REPORT #: S21090702, SWT0025

DECLARATION #: SW22DC124
TEST LAB: Yoke

ITEM TESTED	DESCRIPTION
018-5016	Latitude Pro 7' Dual Web SRL: FS-EX313, Carabiner, Snap Hooks

ADDITIONAL ITEMS CONFORMING UNDER THIS DECLARATION

018-5017, 018-5018, 018-5019, 018-5020, 018-5021, 018-5022, 018-5023, 018-5025, 018-5026, 018-5027, 019-5125, 019-5126, 019-5127, 021-5281, 018-5024, 019-5124, 020-5269, 019-5139, 020-5265, 020-5290, 019-5140, 021-5288, 022-5291

Safewaze declares that the product(s) listed above is in conformity with the requirements of the following standard(s) and/or regulation(s).

ANSI Z359.14-2021, OSHA 1910.140 & 1910.66

ABOVE D-RING USE	STANDARD	ANSI Z359.14-2021 (Class 1)	BELOW D-RING USE	STANDARD	OSHA 1910.140 & OSHA 1910.66
	Max Arrest Force	≤ 1800 lbs. (816.47 kg)		Max Arrest Force	≤ 1800 lbs. (816.47 kg)
Average Arrest Force	≤ 1350 lbs. (612.35 kg)	Average Arrest Force	≤ 900 lbs. (408.23 kg)		
Max Arrest Distance	≤ 42 in. (106.68 cm)	Actual Arrest Distance	≤ 23.6 in. (59.94 cm)		
Actual Arrest Distance	≤ 23 in. (58.42 cm)	Use Below D-ring	2 ft. (.61 m)		
Use Below D-ring	Not permitted	Max Free Fall Distance	48 in. (121.92 cm)		
Max Free Fall Distance	24 in. (60.96 cm)				

CONFORMITY ASSESMENT METHOD	
LEVEL 1: Safewaze lab outside the scope of ISO 17025:2005	
LEVEL 2: Safewaze lab within the scope of ISO 17025:2005	
LEVEL 3: Independent 3rd Party accredited to ISO 17025:2005	X

This certificate is a guarantee that the above standard(s) and/or regulation(s) was met by all requirements. Testing was conducted under normal operation mode. The results of testing apply only to the particular sample tested and to the specific test carried out. This Certificate is only issued for products which have passed the requirements listed in the standard(s) and/or regulation(s).

NAME: Chad Hilliard
SIGNATURE:

TITLE: Testing Director