



Electric Deadman Handle and Cable Assembly



Deadman

DESCRIPTION

This electric deadman handle and cable assembly is used in conjunction with Scully overfill prevention and/or ground verification systems when regulations or operating procedures require the use of an operator held deadman switch.

The rugged deadman handle fits easily in the hand for the maximum in operator comfort. When the trigger is squeezed, an electric switch is activated. The handle itself is constructed of high performance Urethane and includes all stainless steel hardware for corrosion resistance.

A thirty-two-foot, coiled cable with petroleum-resistant, 2-conductor coiled cable is provided for convenient connection to the Sculcon junction box.

TECHNICAL SPECIFICATION

- Handle:** High performance Urethane body with stainless steel trigger.
- Cable:** 32 foot (10.6 meter), coiled cable with petroleum resistant jacket material.
- Switch Specs:** SPST normally open.
- Dimensions:** 4.00L x 1.75D inches (101mm X 44.45mm)
- Weight:** 2 lb (.9kg) including cable.

ORDERING INFORMATION

Description	Part Number
Deadman Handle & Switch Assembly, Blk Coil Cable, 32'	08863
Strain Relief 90Deg 3/8" - Deadman Cable to Sculcon Box	32425

English
April 2021



scully

Scully Signal Company
70 Industrial Way
Wilmington, MA 01887, USA
800 272 8559 • sales@scully.com

Scully Systems Europe NV
Maanstraat 25
2800 Mechelen, Belgium
+32 (0) 15 56 00 70 • info@scully.be

Scully UK Ltd
Meridian House, Unit 33
37 Road One Winsford Industrial Estate,
Winsford Cheshire CW7 3QG, UK
+44 (0) 1606 553805 • sales@scullyuk.com

