

MULTILOAD II

Multiload II is flexible, easy to use and maintain, and is the only preset designed to truly grow with your business.



POWERFUL, FLEXIBLE TECHNOLOGY

Multiload II is the only preset that can boast nearly limitless flexibility (custom logic), extended use (external expansion), and easy breezy maintenance (roomy interior). Multiload II works in standalone mode or connected to wi-fi to send transaction information straight to TMS or most other terminal automation systems. Multiload II delivers straight product or multi-product recipes using ratio, sequential, and various hybrid blending methods.

PROBLEM

Choosing a preset that lacks the ability to grow with your company or support changing configurations often leads to the purchase of unnecessary additional equipment such as extra presets and PLCs. This lack of flexibility also causes cramped space inside the enclosure, making it hard to perform basic maintenance.

Additionally, presets that charge for firmware upgrades could mean missing out on new features. Further, many companies suffer from presets with low security, having limited or no access levels and allowing operators to have passwords like 1111.

SOLUTION

Multiload II units allow more I/O expansion than any other preset, supporting the growth of your company and enabling flexible configurations. Add I/O (FCM units) in an external enclosure rather than purchasing additional blenders, smart injectors, presets or PLCs. This innovative design also means the Multiload II interior is spacious for easy maintenance.

In addition, enjoy free firmware upgrades and rigorous security, with SSL encryption and the ability to have multiple security accounts and levels.

CONTACT US FOR GLOBAL SALES AND SUPPORT



www.toptech.com
TLU - TopTechSales@idexcorp.com

South, Central, and North America
+1 (407) 332-1774
EMEA, Asia, and Oceania
+32 (0)3 250 60 60

USE INTERNAL & EXTERNAL FCM'S TO CONTROL:

**UP TO 12 LOADING
ARMS PER BAY**

**UP TO 5 METERS AND 16
ADDITIVES PER ARM**

FEATURES

BENEFITS

Advanced Additive Control Logic	Enjoy reduced cost and added convenience by eliminating the need for smart injectors
Optimal User-Interface	Full alphanumeric keypad for simplified custom prompting and driver interfacing, plus a color display that is easy to view, even in the sun
Integrated Card Reader	Provides improved security, lowered cost, and increased control
TWIC Ready	TWIC regulations will affect many facilities in the US. Multiload II will help ensure your facility is ready.
Recipe Delivery	Straight product or multi-product recipes using ratio, sequential, and various hybrid blending methods
Multi-lingual Support	All Multiload II units support the English, French, German, Portuguese, Spanish, Simplified Chinese, Traditional Chinese, and Thai languages
Flexible Communications	All Multiload II units offer four communication ports: <ul style="list-style-type: none"> • Serial Ports (3) <ul style="list-style-type: none"> • RS485 4-wire (1) • Selectable RS232/485 4-wire (1) • Selectable full function RS232/485 2-wire (1) • 10/100 Mb Ethernet (1)

ENCLOSURE OPTIONS

FIRMWARE OPTIONS

EXL - Division 1	Division 2	Standard	SMP	SCS	Slate
		Control 12 loading arms per bay, 1-5 meters, & 16 additives per load arm	Control 1 loading arm per bay, 1 meter, & 1-2 additives per load arm	Handles loading and unloading for crude skids, including 1 meter, 20 sample pots, and pipeline injection	Uses your prompts & database to give company specific information

**CONTACT US FOR GLOBAL
SALES AND SUPPORT**



www.toptech.com
TLU - ToptechSales@idexcorp.com

South, Central, and North America
+1 (407) 332-1774
EMEA, Asia, and Oceania
+32 (0)3 250 60 60