



## Latitude HD 11' Web SRL-P

\*See chart for part numbers, hook configurations, and product weights

### FEATURES :

- Reliable internal braking system eliminates need for external shock pack.
- Durable housing and premium webbing increase strength and longevity.
- 360/180° attachment point offers full range of motion.
- Single leg and dual leg options available.
- Available with various hook options, see chart.
- All components are Z359.12 compliant.



Class  
**1**  
Anchor at or above dorsal D-ring

Product shown:  
FS-FSP14095-W

| USER WEIGHT CAPACITY |                            |
|----------------------|----------------------------|
| ANSI                 | 130-310 lbs. (59-140.6 kg) |
| OSHA                 | Up to 420 lbs. (190.5 kg)  |

| STANDARD COMPLIANT WITH |                   |
|-------------------------|-------------------|
| ANSI                    | Z359.14-2021      |
| OSHA                    | 1910.140, 1910.66 |

| ANSI CLASS 1 (ABOVE D-RING)                            |                         |
|--|-------------------------|
| Max. arrest force                                      | ≤ 1,800 lbs. (816.5 kg) |
| Avg. arrest force                                      | ≤ 1,350 lbs. (612.4 kg) |
| Max. arrest distance                                   | ≤ 42 in. (107 cm)       |
| Actual arrest distance                                 | ≤ 26 in. (66 cm)        |
| Max. free fall distance                                | 24 in. (61 cm)          |
| Use below d-ring                                       | <b>NOT PERMITTED</b>    |
| Min. required fall clearance                           | 6 ft. 2 in. (1.9 m)     |
| For full clearance requirements, see user instructions |                         |

| OSHA (BELOW D-RING)                                    |                         |
|--|-------------------------|
| Max. arrest force                                      | ≤ 1,800 lbs. (816.5 kg) |
| Avg. arrest force                                      | ≤ 900 lbs. (408.2 kg)   |
| Max. arrest distance                                   | N/A                     |
| Actual arrest distance                                 | ≤ 18.5 in. (47 cm)      |
| Max. free fall distance                                | 72 in. (183 cm)         |
| Use below d-ring                                       | 3 ft. (0.91 m)          |
| Min. required fall clearance                           | 9 ft. 6 in. (2.9 m)     |
| For full clearance requirements, see user instructions |                         |

| MATERIAL SPECIFICATION |  |
|------------------------|--|
| Webbing                | 25mm UHMPE webbing                                       |
| Housing                | Aluminum   |
| Bracket                | Steel, aluminum (dependent on configuration)             |
| Hook options           | Steel, aluminum, dielectric (dependent on configuration) |

