

MULTILOAD II+

Multiload II+ is a powerful preset that interfaces with virtually all load rack equipment and provides one place for configuration, logs, storage, and more. Multiload II+ is compatible with all current and future Toptech production software.



POWERFUL, FLEXIBLE TECHNOLOGY

Multiload II+ is the only preset that can boast nearly limitless flexibility (custom logic), extended use (external expansion), and easy breezy maintenance (replace FCMs without even turning a screwdriver). Multiload II+ works in standalone mode or through ethernet ports and serial ports to send transaction information straight to TMS or most other terminal automation systems. Multiload II+ is ready to support alternative fueling applications and delivers straight product or multi-product recipes using ratio, sequential, and various hybrid blending methods.

PROBLEM

Choosing a preset that lacks the ability to grow with your company or support changing configurations often leads to the purchase of unnecessary additional equipment such as extra presets and PLCs. Plus, when it's time to perform maintenance, the space inside is often cramped, making it difficult to maneuver within the device.

Additionally, expensive firmware upgrades could mean missing out on new features. Further, it's often hard to find the cause of issues, making it difficult to manage your load racks and support your drivers.

SOLUTION

Multiload II+ units have internal FCM mounting to support nearly any single or double arm configuration. If more I/O points are needed, Multiload II+ even allows external FCMs to avoid purchasing more blenders, smart injectors, presets or PLCs. Plus, hinge-mounted internal components and additional cable glands make it easy to perform maintenance within your units.

In addition, enjoy free firmware upgrades and expansive support features which make it easy to quickly identify and correct issues at the load rack.

CONTACT US FOR GLOBAL SALES AND SUPPORT



www.toptech.com
TLU - ToptechSales@idexcorp.com

South, Central, and North America
+1 (407) 332-1774
EMEA, Asia, and Oceania
+32 (0)3 250 60 60

USE INTERNAL & EXTERNAL FCM'S TO CONTROL:

***UP TO 12 LOADING ARMS PER BAY**

UP TO 5 METERS AND 16 ADDITIVES PER ARM

FEATURES

BENEFITS

Advanced Additive Control Logic	Enjoy reduced cost and added convenience by eliminating the need for smart injectors
Optimal User-Interface	Large alphanumeric keypad with intuitive navigation and proven longevity tactile feedback. Plus, drivers will appreciate the 10.4" full color display.
Integrated Card Reader	An attached card reader provides superior security, cost savings, and control. Plus, it is securely side-mounted to accommodate the unit's large screen and keypad.
Recipe Delivery & Blending	Straight product or multi-product recipes using ratio, sequential, and various hybrid blending methods. One Multiload II+ unit can dispense an endless number of products. Multiload II+ is equipped to handle all your blending needs, including alternative fuels.
Multi-lingual Support	All Multiload II+ units support the English, French, German, Portuguese, Spanish, Simplified Chinese, Traditional Chinese, and Thai languages
Flexible Communications	All Multiload II+ units offer the following communication ports: <ul style="list-style-type: none"> • Serial Ports (4) <ul style="list-style-type: none"> • Selectable RS232/485 2/4-wire (3) • Selectable full function RS232/485 2/4-wire (1) • 10/100/1000 Mb Ethernet (2)

ENCLOSURE OPTIONS

FIRMWARE OPTIONS

Ex	Division 2	Standard	SMP	SCS	Slate
		Control 12 loading arms per bay, 1-5 meters, & 16 additives per load arm	Control 1 loading arm per bay, 1 meter, & 1-2 additives per load arm	Loading and unloading for crude skids, including 1 meter, 20 sample pots, and pipeline injection	Use your prompts & database to give company specific information

*Multiload II+ controls up to 12 arms per bay when truck loading and unloading. Please contact us for information about railcar loading and unloading.

CONTACT US FOR GLOBAL SALES AND SUPPORT



www.toptech.com
 TLU - ToptechSales@idexcorp.com

South, Central, and North America
 +1 (407) 332-1774
 EMEA, Asia, and Oceania
 +32 (0)3 250 60 60