



## DECLARATION OF CONFORMITY

**DECLARATION DATE:** 12/30/22  
**TEST REPORT #:** L22042501, SWT0028

**DECLARATION #:** SW22DC120  
**TEST LAB:** Yoke

ITEM TESTED	DESCRIPTION
FS-FSP14095-W	Latitude HD 11' Dual Web SRL: FS-EX313, Carabiner, Snap Hooks

ADDITIONAL ITEMS CONFORMING UNDER THIS DECLARATION
FS-FSP14095-W-RBH

Safewaze declares that the product(s) listed above is in conformity with the requirements of the following standard(s) and/or regulation(s).

### ANSI Z359.14-2021, OSHA 1910.140 & 1910.66

ABOVE D-RING USE	STANDARD	ANSI Z359.14-2021 (Class 1)	BELOW D-RING USE	STANDARD	OSHA 1910.140 & OSHA 1910.66
	Max Arrest Force	≤ 1800 lbs. (816.47 kg)		Max Arrest Force	≤ 1800 lbs. (816.47 kg)
Average Arrest Force	≤ 1350 lbs. (612.35 kg)	Average Arrest Force	≤ 900 lbs. (408.23 kg)		
Max Arrest Distance	≤ 42 in. (106.68 cm)	Actual Arrest Distance	≤ 18.5 in. (47.0 cm)		
Actual Arrest Distance	≤ 26 in. (66.04 cm)	Use Below D-ring	3 ft. (.91 m)		
Use Below D-ring	Not permitted	Max Free Fall Distance	72 in. (182.9 cm)		
Max Free Fall Distance	24 in. (60.96 cm)				

CONFORMITY ASSESMENT METHOD	
LEVEL 1: Safewaze lab outside the scope of ISO 17025:2005	
LEVEL 2: Safewaze lab within the scope of ISO 17025:2005	
LEVEL 3: Independent 3rd Party accredited to ISO 17025:2005	<b>X</b>

This certificate is a guarantee that the above standard(s) and/or regulation(s) was met by all requirements. Testing was conducted under normal operation mode. The results of testing apply only to the particular sample tested and to the specific test carried out. This Certificate is only issued for products which have passed the requirements listed in the standard(s) and/or regulation(s).

**NAME:** Chad Hilliard  
**SIGNATURE:**

**TITLE:** Testing Director