



# IECEX Certificate of Conformity

## INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit [www.iecex.com](http://www.iecex.com)

Certificate No.: IECEx BAS 17.0019X

Issue No: 4

Certificate history:

Status: **Current**

Issue No. 4 (2019-08-27)

Issue No. 3 (2019-04-11)

Date of Issue: **2019-08-27**

Page 1 of 4

Issue No. 2 (2018-02-12)

Issue No. 1 (2017-10-20)

Issue No. 0 (2017-05-05)

Applicant: **Emerson - Rosemount, Micro Motion Inc.**  
12001 Technology Drive  
Eden Prairie  
MN 55344  
**United States of America**

Equipment: **Model 8800D Vortex Flowmeter**

Optional accessory:

Type of Protection: **Protection by Enclosure 'tb'**

Marking: **Ex tb IIIC T85°C Db (-20°C ≤ Ta ≤ +70°C)**

Approved for issue on behalf of the IECEx  
Certification Body:

R.S. Sinclair

Position:

Technical Manager

Signature:  
(for printed version)

Date:

27-8-19

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting the [Official IECEx Website](http://www.iecex.com).

Certificate issued by:

**SGS Baseefa Limited**  
Rockhead Business Park  
Staden Lane  
Buxton, Derbyshire, SK17 9RZ  
United Kingdom



# IECEX Certificate of Conformity

Certificate No: IECEx BAS 17.0019X Issue No: 4  
Date of Issue: 2019-08-27 Page 2 of 4  
Manufacturer: **Emerson - Rosemount , Micro Motion Inc.**  
12001 Technology Drive  
Eden Prairie  
MN 55344  
**United States of America**

Additional Manufacturing location(s):

**SC Emerson SRL**  
Emerson Street No. 4  
400641 Cluj-Napoca  
Romania

**Emerson Process Management Flow  
Technologies Co., Ltd.**  
111, Xing Min South Road  
Jiangning District, Nanjing  
Jiangsu Province  
211100  
China

**F-R Tecnologías De Flujo, S.A. De C.V.**  
Rosemount Flow Business Unit  
Ave. Miguel de Cervantes 111  
31136 Chihuahua  
Mexico

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

**STANDARDS:**

The apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

**IEC 60079-0 : 2017** Explosive atmospheres - Part 0: Equipment - General requirements  
Edition:7.0  
**IEC 60079-31 : 2013** Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"  
Edition:2

*This Certificate **does not** indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.*

**TEST & ASSESSMENT REPORTS:**

*A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in*

Test Report:

[GB/BAS/ExTR17.0032/00](#) [GB/BAS/ExTR17.0223/00](#) [GB/BAS/ExTR17.0375/00](#)  
[GB/BAS/ExTR19.0066/00](#) [GB/BAS/ExTR19.0207/00](#)

Quality Assessment Report:

[NO/PRE/QAR15.0018/01](#) [NO/PRE/QAR15.0031/01](#) [NO/PRE/QAR16.0019/01](#)



# IECEX Certificate of Conformity

Certificate No: IECEx BAS 17.0019X

Issue No: 4

Date of Issue: 2019-08-27

Page 3 of 4

## Schedule

### EQUIPMENT:

*Equipment and systems covered by this certificate are as follows:*

The Model 8800D Vortex Flowmeter is a two-wire, piezoelectric-based flowmeter designed to measure the flow of fluid within a pipe.

It consists of four printed circuit boards (PCB's), a terminal block and an optional liquid crystal display unit mounted within a coated aluminium alloy or stainless steel enclosure forming the transmitter assembly. This is either mounted on a stainless steel, nickel alloy, carbon steel or super duplex meter body, or connected via a coaxial cable to a remote meter body which contains the piezoelectric sensor.

The transmitter converts the sensor input to a 4-20mA output, HART digital output or pulse totalizer signal output. The transmitter can be fitted with an alternative Fieldbus output board to form Foundation Fieldbus variants of the Model 8800D Vortex Flowmeters.

Connection to external circuit is achieved by the use of a 4-way terminal block within the transmitter enclosure, entry to which is gained by a threaded conduit entry points. The installation of external connections and the plugging of the unused entry must be carried out using appropriate Ex e or Ex t cable glands or blanking plug components with a minimum degree of protection of IP66 certified by an approved certification body.

The input parameters of the different variants of the equipment are as follows: -

#### **Model 8800D 4-20mA HART Vortex Flowmeter**

Maximum Working Voltage = 42V d.c.

#### **Model 8800D Foundation Fieldbus Vortex Flowmeter**

Maximum Working Voltage = 32V d.c.

Four variants of the above Model 8800D Vortex Flowmeters can be mounted on process pipework to form the Model 8800DQ Quad Vortex Flowmeter. Each Model 8800D Vortex Flowmeter mounted to the arrangement has the same input parameters as identified above.

### **SPECIFIC CONDITIONS OF USE: YES as shown below:**

1. The enclosure may be made from aluminium alloy with a protective polyurethane paint finish which may constitute a potential electrostatic ignition risk. Care should be taken to protect it from external conditions conducive to the build-up of electrostatic charge on such surfaces. The enclosure must not be rubbed or cleaned with a dry cloth.
2. When the equipment is installed, particular precautions must be taken to ensure, taking into account the effect of process fluid temperature, that the ambient temperature of the electrical housing of the equipment meets the marked protection type temperature range.



# IECEX Certificate of Conformity

Certificate No: IECEx BAS 17.0019X

Issue No: 4

Date of Issue: 2019-08-27

Page 4 of 4

## DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

### Variation 4.1

To permit the fitting of four Model 8800D Vortex Flowmeters onto a common process pipework to form the Model 8800DQ Quad Vortex Flowmeter. The four flowmeters fitted can be either the fixed or remote mounted variants of the Model 8800D and be a mixture of HART or Foundation Fieldbus variants of the equipment. The certification and input parameters to each Model 8800D remain as previously assessed.

The Equipment Schedule on page 3 of the certificate was revised to detail the Model 8800DQ variant.

ExTR: **GB/BAS/ExTR19.0207/00**

File Reference: **19/0417**